

Iso A-Clean 50 %

PRODUCT DESCRIPTION Water-dilutable cleaning product

PROPERTIES

- Removes coatings, inhibits growth and removes micro-organisms and bacteria from outdoor surfaces. Achieves its maximum effect within 3 – 4 days

USE Iso A-Clean is to be used on outside surfaces, such as:

- Roofs
- Facades
- Paving stones
- Skylight windows
- Plinth courses and walls

Not to be used on solar cells without the accept of the supplier of the solar cells

TECHNICAL DATA

Composition	Water Quaternary ammonium compounds (alkyl(C12-16)Dimethylbenzyl-ammonium chloride)
Concentration	50 % (to be diluted to 1 – 2 %)
Packaging sizes	5 l, 25 l, 200 l, 1000 l
Spreading rate	2 - 6 m ² /l
pH	7 - 8
Density	1 kg/l

Spreading rate 2 – 6 m²/l in ready-to-use solution (1 – 2 %)

The practical spreading rate depends on the condition of the substrate

Storage Cool, protected from frost, in tightly closed packaging, and out of reach of children

APPLICATION DETAILS

Pre-treatment/cleaning Clean using high-pressure. Apply Iso A-Clean in ready-to-use solution when the surface is dry. If Iso A-Clean is used for ordinary maintenance, a pre-treatment is not necessary.

Application conditions The temperature must be between 5° C and 30° C

Application method Use protective gloves, safety glasses, and respirator during application.
Apply with paintbrush, brush or sprayer (high/low pressure)
When cleaning vertical surfaces, it is recommended to use a low-pressure sprayer in addition to paintbrush and brush
Only apply Iso A-Clean until the surface is saturated

All excess liquid must be collected. Do not channel into the ground, streams, or drains.

Always make a test coat to ensure the compatibility of product and surface.

Iso A-Clean 50 %

Stirring	Not to be stirred
Dilution	Iso A-Clean is supplied as a concentrate - Ready-to-use solution for very dirty surfaces: 1 part of Iso A-Clean to 25 parts of water (2 % solution) - Ready-to-use solution for ordinary maintenance and cleaning before painting: 1 part of Iso A-Clean to 50 parts of water (1 % solution) <u>The use of a higher concentration will not increase the effectiveness of Iso A-Clean</u>
Cleaning of equipment	Rinse with water

ENVIRONMENT Avoid spillage into drains, water systems and soil. Destroy liquid waste according to the local regulations. Recycle or dispose of empty, dry cans in accordance with local regulations
VOC: Max. 30 g/l (Kat. A/h)

CONTACT Iso Paint Nordic A/S (Tikkurila Danmark A/S), Tvaervej 8, DK-6640 Lunderskov
mail.isopaint@tikkurila.com

The above information is only intended as a guide, it is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience with the products. We reserve the right to change the information without notice. The quality of the products is ensured by Tikkurila's operational systems, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that may have an effect on the use and application of the product. The product is meant for professional use and should only be used by professionals with the necessary knowledge of the product and expertise in the correct use of the product. We disclaim liability for any damages caused by using the product against Tikkurila's instructions including e.g. demands as to storage, surface, and weather conditions, or by using the product for inappropriate purposes. To the extent that the legislation in force allows it, we refuse to take responsibility for the conditions under which the product is used, or for the use or the application of the product. If the product is used for other purposes than recommended in this data sheet – without obtaining our prior written confirmation of the product being usable for this – this use is on one's own risk.