


Colowood

DESCRIPTION	Water-borne filler for wooden surfaces.
PRODUCT FEATURES	For filling holes in interior wooden surfaces such as fibre boards, solid wood or veneer.
RECOMMENDED USES	Recommended for furniture, doors, panel walls and ceilings.



 [zoom](#)

TECHNICAL DATA



Colour Range	Birch, birch knot, pine, pine knot, oak, oak knot, beech, white, mahogany and black.
Coverage	Practical coverage depends on the application method, conditions and the shape and roughness of the surface to be treated.
Thinner	Water
Application method	By spatula.
Drying times	Thin filling layer can be sanded after 4 hours and deeper filling layer after 24 hours.
Solids volume	Abt. 64±2 % by volume, 82±2 % by weight.
Density	2,0 ± 0,2 kg/ litre
Product code	007 2074, 007 2075, 007 2076, 007 2077, 007 2078, 007 2079, 007 2080, 007 2081, 007 2083, 007 2209.

APPLICATION DETAILS

Application conditions	The surface to be treated must be dry, the temperature of the air at least +5°C and the relative humidity of the air below 80%.
Preparation	Remove dirt from the surface. Brush away dust and loose material.
Application	Apply with a spatula. Thin with water, if necessary. Fill large holes preferably twice or several times. Sand the surface and remove sanding dust.
Surface treatment	Can be recoated with Tikkurila's water-borne, water-borne UV and solvent-borne products.
Mixing of components	Thin filler to the viscosity required.
Cleaning of tools	Water.
EU VOC 2004/42/EC-limit value	The Volatile Organic Compounds amount is 22 g/litre of putty. VOC content of the putty (thinned 10 % by volume) is 20 g/l.

HEALTH AND SAFETY LABELLING according to	Containers are provided with safety labels, which should be observed. Further information about hazardous influences and protection are detailed in individual health and safety data sheets. A health and safety data sheet is available on request from Tikkurila Oyj. For industrial and professional use only.
--	--

 [Safety data sheet](#)



Colowood

Regulation (EC)
No. 1272/2008

ENVIRONMENTAL
and WASTE -
DISPOSAL
TRANSPORT -
-

The above information, based on laboratory tests and practical experience, has been proved valid at the date marked on the product data sheet. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As a manufacturer we cannot be responsible for any damages caused by using the product against our instructions or for inappropriate purposes.