



TIKKURILA

LAKKAKITTI

FILLER STOPPER

DESCRIPTION

Alkyd filler.

RECOMMENDED USES

Furniture, doors, holes and indentations on walls, doors, window frames, etc. Machinery, equipment, boats, vehicles, etc.

PRODUCT FEATURES

For interior and dry exterior surfaces, smoothing and filling wood, woodfiber board, chipboard and metal surfaces according to the directions for use. Ideal for use with latex, alkyd, oil and catalyzed paints. The surface is easy to dry- and wet-sand and scrape.



LAKKAKITTI

TECHNICAL DATA

Colour Shades	White
Can sizes	0.333 l, 1 l, 3 l
Application method	Application with a smoothing trowel.
Drying time (23°C and 50% relative air humidity)	From 30 minutes to a few hours, depending on the layer thickness, temperature, relative air humidity and material being filled.
Density (kg/l)	1.8 kg/l, ISO 2811
Volume solids (%)	74
Storage	Unaffected by cold storage or transportation. Protect from frost

LAKKAKITTI

APPLICATION INSTRUCTIONS

Application conditions

The surface to be leveled must be dry, the ambient temperature at least +5 °C and the relative humidity of air below 80%.

Surface preparation

Unpainted surfaces:

Remove dirt, dust and loose material. Adhesion will be improved by priming porous surfaces with Helmi Primer.

Previously painted surfaces:

Wash the surface with Kalustepesu or Maalipesu cleaning agent. Once the surface is dry, remove as much paint as you can with a scraper and sand the entire surface. Remove the sanding dust.

Application

Apply directly onto wood, chipboard, woodfiber board or metal surfaces or on dry primer with a trowel. It is usually enough to only fill holes, irregularities and rough patches and level small areas. Lakkakitti does not normally need to be thinned for application by trowel. You can paint over Lakkakitti with primers and intermediate and finishing paints containing strong solvents, or with regular water-borne and solvent-borne paints.

Coating

Finish the surfaces with ordinary alkyd or waterborne paints, also solventborne priming, undercoating or finishing paints can be used for finishing.

Cleaning of tools

Clean tools with White Spirit 1050.

Environmental and waste disposal

Avoid spillage into drains, water systems and soil. Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations.

HEALTH AND SAFETY LABELLING according to Regulation (EC) No. 1272/2008

WARNING. Flammable liquid and vapor. Harmful to aquatic life with long lasting effects. Contains ethyl methyl ketoxime. May produce an allergic reaction. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from sparks and open flames. - No smoking. Avoid breathing vapor. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves.



GHS02

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.