



# Helmi Furniture Filler - New Product

<b>DESCRIPTION</b>	Water-borne special furniture filler.
<b>PRODUCT FEATURES</b>	For filling small holes prior to finishing painting, for new as well as previously painted surfaces. Filling capacity 3 mm.
<b>RECOMMENDED USES</b>	Fixtures, furniture, doors, windows and other dry interior wood surfaces.



## TECHNICAL DATA



Colour Range	White
Can sizes	200 ml
Thinner	Water
Application method	Application by trowel
Drying time at 23°C and 50% relative air humidity	Thin filling layer (1 mm) can be sanded after approx. 1 hour. Drying time depends on layer thickness, relative humidity of the air and temperature.
Filling capacity	Max. 3 mm
Solids volume	74 %.
Density	1.7 kg/l, ISO 2811
Storage	Protect from frost. Store in dry and cool place, protected from sunlight.

## APPLICATION DETAILS

Application conditions	The surface to be treated must be dry, the temperature of the air at least +10°C, and the relative humidity of the air below 80 %.
Preparation	Unpainted surface: Clean the surface from dirt. Dust off and remove loose particles. Apply Presto Furniture Filler with a trowel.  Previously painted surface: Clean previously painted surfaces with Kalustepesu cleaning agent. After the surface has dried, remove flaking paint and sand the paint surfaces until matt. Remove sanding dust.
Smoothing	Apply Helmi Furniture Filler with a smoothing trowel. Apply on bigger holes rather two or three times. Sand the surface and remove sanding dust. Finishing painting can be done with a water-borne or alkyd paint.
Cleaning of tools	Clean tools with water.

**HEALTH AND SAFETY LABELLING** according to Regulation (EC) No. 1272/2008 The product is not classified as dangerous. Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Wear protective gloves. A Material Safety Data Sheet is available on request.

**ENVIRONMENTAL and WASTE DISPOSAL** Recycle empty, dry cans or dispose them of in accordance with local regulations.

**TRANSPORT** not classified

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

[Back](#)