

IMPREGNA- TION FOR WATER AND HORIZONTAL SURFACES



ISO PAINT
NORDIC^{A/S}

INVISIBLE SHIELD
THAT PROTECTS
AGAINST MOISTURE



ISO PAINT
NORDIC 1/2

Manufacturer's recommendation: In order to maintain a clean and attractive surface, it is recommended to maintain treated surfaces with ISO A-CLEAN every 1-2 years as necessary.

IMPREGNATION: AN INVISIBLE SHIELD AGAINST MOISTURE

Surfaces that are protected against water penetration are a poor breeding ground for moss and algae and are exposed to less frost damage. If moist surfaces are not treated, they will eventually become discoloured. Iso Paint Nordic has developed waterproofing products that provide good surface protection and facilitates the maintenance of roofs, façades and tiling.

We have several solutions that protect vertical and horizontal surfaces from wind and weather.

And without applying layer after layer of new paint. The impregnation is designed for those who want to preserve the original natural look. The waterproofing products bond actively with mineral surfaces and are optically invisible.

The impregnation's water repellent effect prevents stains and dirt and reduces the risk of salt efflorescence and frost damage.

FACTS ABOUT HYDROBLOCK AND PROCOVER

- *Protects against water*
- *Keeps the surface dry*
- *Self-cleaning effect*
- *Energy-saving*
- *Very long lifetime*

YOU IMPREGNATE YOUR SHOES. WHAT ABOUT YOUR HOUSE? HYDROBLOCK IS JUST AS STRONG AS IT IS INVISIBLE. HYDROBLOCK CAN PROTECT YOUR ROOF, YOUR TILES, YOUR WALLS AND ALL OTHER OUTDOOR SURFACES.

INTELLIGENT PROTECTION

HydroBlock protects against cracking caused by frost, water and other elements that damage the building surfaces.

ENERGY EFFICIENT

Tested by the Danish Technological Institute and others for its energy-saving properties.





HYDROBLOCK WB

Suitable for: Paving stones, tiles, façades, warehouses and bridge constructions of mineral origin, such as brick, limestone, mortar, sandstone, granite and mineral plasters

May not be used on: Windows (windows should be covered during treatment of façades)

Significant product characteristics: Water-repellent surface, high water pearlescent effect, permits water vapour inside the structure to pass through, reduces salt extraction to the surface, does not form a film, preventing frost damage and inhibits the growth of algae and green coatings.
Colours: Colourless



PROCOVER WB

Suitable for: mineral surfaces such as sandstone, concrete, terrazzo, tile, limestone, paving stone and slabs.

May not be used on: Windows (windows should be covered during treatment of façades)

Significant product characteristics: Water and grease/oil repellent surface that inhibits the growth of algae and green coatings. The surface is vapour permeable and does not form a film, while reducing the risk of frost damage.

Colours: Colourless

Iso Paint Nordic recommends the following products for waterproofing:

HYDROBLOCK WB

water-based, especially for surfaces exposed to water and moisture

PROCOVER WB

water-based, especially for horizontal surfaces exposed to water, oil and grease

HYDROBLOCK SB

solvent-based, especially for hard and impervious mineral surfaces, such as marble

PROCOVER SB

solvent-based, used on hard and impervious surfaces, such as marble, which is exposed to water, oil and grease



Contact your specialist in surface treatment:

Tvaervej 8
6640 Lunderskov, Denmark
www.isopaint.com