




DESCRIPTION Water-borne, solventfree dispersion paint for professional interior painting. Semi-matt renovation paint with Nordic ecolabel. Wide range of colours. High solids mid sheen emulsion for interior walls and ceilings.

PRODUCT FEATURES Suitable for painting of new and already treated concrete, plaster, filler, plasterboard, chipboard and wood fibreboard surfaces according to instructions.

RECOMMENDED USES Walls and ceilings in dry interior premises, e.g. living rooms, kitchens, offices and public spaces exposed to light wear.

[zoom](#)**TECHNICAL DATA**

Base paints A and C
Colour Range Colours tinted according to Tikkurila Symphony 2436 colour card.
Gloss grade Semi-matt
Coverage For absorbing surfaces 5-7 m²/l. For non-absorbing surfaces 9-11 m²/l.
Can sizes A-base: 2.7 L, 9 L, 18 L, C-base: 9 L, 18 L
Thinner Water
Roller, brush or spray.

Application method
Airless spray:
- nozzle 0,017" - 0,021"
- thinning 0-10 vol.-%

Drying time at 23°C and 50% relative air humidity
Dust dry after half an hour.
Recoatible after 1-2 hours.

Wet scrub resistance SFS-EN 13300 class II, ISO 11998.

Heat resistance 85°C, ISO 4211-3.

Chemical resistance Withstands cleaning chemicals and weak solvents, such as White Spirit.

Solids volume approx. 36 % depending on the colour.



Nova 20

| | |
|--------------|--|
| Density | 1.3 kg/l, ISO 2811 |
| Storage | Protect from frost. Store in dry and cool place, protected from sunlight. Tinted paint or opened can does not withstand long-term storage. Close the lid carefully for next use. |
| Product code | 17V-s. |

APPLICATION

DETAILS

| | |
|--------------------------|--|
| Application conditions | <p>The surface to be painted must be dry, the temperature of the air at least +5 °C, and the relative humidity of the air below 80 %.</p> <p>Unpainted surfaces: Remove dirt and dust from the surfaces. Fill the surfaces with a suitable Tikkurila Presto or Prestonit filler, if needed, and sand the dried surface. Remove sanding dust. Prime with Nova 2 or Ykköspohja.</p> |
| Preparation | <p>Previously painted surfaces: Wash down surfaces with diluted Maalipesu cleaning detergent and rinse carefully with water. Sand hard and glossy surfaces matt and remove sanding dust. Fill cracks and holes with a suitable Tikkurila Presto or Prestonit filler and sand the dried surface. Remove sanding dust. Prime with Nova 2 or Ykköspohja, if needed.</p> |
| Painting | <p>Stir Nova 20 well before use and thin with water, if necessary. Apply 1-2 times with a roller, spray or brush.</p> <p>Remove the excess paint from tools before cleaning with water. Tikkurila</p> |
| Cleaning of tools | <p>Pensselipesu (Tool Cleaner) is recommended to be used for cleaning hardened paint.</p> <p>Cleaning earliest approx. 1 month after painting, if needed.</p> <p>Surfaces are cleaned with a damp cleaning tool moistened in a neutral (pH 6-8) washing solution. Very dirty surfaces are cleaned with a weakly alkaline (pH8-10) washing solution. The surface may not remain wet after cleaning. Follow the dilution instructions given by the detergent manufacturer.</p> |
| Maintenance instructions | <p>The product achieves its final hardness and durability after one month under normal conditions, therefore the surfaces must be handled with care during this time. If the surfaces need to be cleaned soon after finishing, clean them gently with a damp cleaning cloth.</p> |
| Maintenance treatment | <p>Surfaces painted with Nova 20 can be recoated with same type of water-borne paint. See preparation.</p> |



Nova 20

EU VOC 2004/42/ (cat A/a) 30g/l(2010)

EC-limit value Nova 20 contains VOC max. 30g/l.

HEALTH AND SAFETY

Contains 1,2-benzisothiazol-3(2H)-one and 5-chloro-2-methyl-2H-isothiazol-3-on/2-methyl-2H -isothiazol-3-one (3:1). May produce an allergic reaction. Wear protective gloves. A Safety Data Sheet is available on request.

LABELLING

according to

Regulation (EC)  [NOVA 2, 7, 12, 20](#)

No. 1272/2008

ENVIRONMENTAL and WASTE Empty cans should be recycled or disposed of in accordance with local regulations. Liquid waste should be destroyed according to the local regulations.

DISPOSAL  [Ympäristöseloste](#)

TRANSPORT ADR: not classified

sre111113 / linla170613 / nlear121113 / pih170613 / 17V-s
