

# NON-SLIP Agent

<b>DESCRIPTION</b>	Additive consisting of hollow, lightweight silicate microspheres with a maximum grain size of approximately 300 µm.
<b>EXAMPLES OF USE</b>	Particularly suitable for use as a non-slip agent for Tikkurila roof paints or floor coatings, e.g.  Aki Garage Coating, Akvaccoat, Betolux, Betolux Akva, Novopox, Panssarimaali, Panssari Akva, Permo floor paint.
<b>TECHNICAL DATA</b>	
<b>Colour</b>	Grey.
<b>Packaging</b>	1/3 L
<b>Melting temperature</b>	1200 - 1350 °C.
<b>Hardness</b>	5 on the Mohs scale.
<b>Bulk density</b>	approx. 0.4 g/cm <sup>3</sup>
<b>Storage</b>	Keep the package tightly closed to protect it from dusting and wetting.
<b>INSTRUCTIONS</b>	
<b>Treatment</b>	At least two paint layers have to be applied when using the Non-Slip Agent. The Non-Slip powder is added in the top coat layer. Mixing ratio: 1/3 litres of Non-Slip powder is added into 10 litres of paint. Accordingly less than a third of 1/3 l package is added into 3 litres of paint. See more detailed instructions and mixing ratio in the Product Data Sheet of the paint to be used.
<b>HEALTH AND SAFETY CLASSIFICATION</b> according to EC Directive 99/45/EC	The product is not classified as dangerous. A Safety Data Sheet is available on request.
<b>WASTE DISPOSAL</b>	Recycle empty, dry cans or dispose them of in accordance with local regulations.
<b>TRANSPORT</b>	not classified

sre110413/niear260811/007 9200