

Temadur Accelerator

DESCRIPTION An accelerator solution which makes the curing faster.

PRODUCT FEATURES Used to accelerate the curing of TEMADUR 20, 50 and 90 polyurethane paints and TEMADUR CLEAR varnish. Facilitates early taping of painted surfaces. Not suitable for TEMADUR HB polyurethane paints.

Recommended uses -

TECHNICAL DATA

Coverage Recommended usage max. 10 vol.-% of the amount of the paint/hardener mixture.

Drying times Influence on drying times

Amount of accelerator, + 23 °C	0 %	5 %	10 %
Pot life	4 h	1 h	½ h
Tapeable	24 h	8 h	4 h

Density 0.9 kg / l

Shrinkage and cracking 990 0746

Temadur Accelerator

APPLICATION DETAILS

Treatment Mix base and hardener. Add the required amount of accelerator. Thin with Thinner 1048, if necessary, and mix thoroughly. Pay attention to the shortened pot life and start the painting work without delay.

HEALTH AND SAFETY LABELLING according to Regulation (EC) No. 1272/2008

Containers are provided with safety labels, which should be observed. Further information about hazardous influences and protection are detailed in individual health and safety data sheets. A health and safety data sheet is available on request from Tikkurila Oy. For professional use only.

Safety data sheet  [TEMADUR ACCELERATOR \[GB-ENG\]](#)

[Back](#)