



SAFETY DATA SHEET

KILPI TIILIKATTOMAALI (new quality)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : KILPI TIILIKATTOMAALI (new quality)
Product description : A waterborne acrylate paint.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Painting

1.3 Details of the supplier of the safety data sheet

Manufacturer or Distributor

Tikkurila Oyj
P.O. Box 53
FI-01301 VANTAA
FINLAND
Telephone +358 20 191 2000

e-mail address of person responsible for this SDS : Tikkurila Oyj,
Product Safety,
e-mail: productsafety@tikkurila.com

1.4 Emergency telephone number

Telephone number : 112
(24h)

Supplier or Manufacturer

Telephone number : Tikkurila Oyj
+358 20 191 2000 (GMT +2) Mon-Fri 8-16

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

2.2 Label elements

Signal word : No signal word.

Hazard statements : H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

General : Not applicable.

Prevention : P273 - Avoid release to the environment.

Response : Not applicable.

Storage : Not applicable.

Disposal : Not applicable.

Supplemental label elements : Contains 1,2-benzisothiazol-3(2H)-one (BIT), 2-Octyl-2H-isothiazol-3-one (OIT) and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M)IT/MIT (3:1)). May produce an allergic reaction.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Treated articles

This product contains a biocidal product for the preservation of the product during storage. Contains C(M)IT/MIT (3:1). Wear protective gloves.

2.3 Other hazards

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification Regulation (EC) No. 1272/2008 [CLP]	Notes
2-(2-butoxyethoxy)ethanol	REACH #: 01-2119475104-44 EC: 203-961-6 CAS: 112-34-5 Index: 603-096-00-8	≤3	Eye Irrit. 2, H319	-
propylene glycol	REACH #: 01-2119456809-23 EC: 200-338-0 CAS: 57-55-6	≤3	Not classified.	-
ammonia	REACH #: 01-2119488876-14 EC: 215-647-6 CAS: 1336-21-6 Index: 007-001-01-2	≤0.3	Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400 (M=1)	B
1,2-benzisothiazol-3(2H)-one (BIT)	EC: 220-120-9 CAS: 2634-33-5	<0.05	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411	-
terbutryn	EC: 212-950-5 CAS: 886-50-0	≤0.021	Acute Tox. 4, H302 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)	-
2-Octyl-2H-isothiazol-3-one (OIT)	EC: 247-761-7 CAS: 26530-20-1 Index: 613-112-00-5	≤0.011	Acute Tox. 4, H302 Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)	-
zinc pyrithione	REACH #: 01-2119511196-46 EC: 236-671-3 CAS: 13463-41-7	≤0.011	Acute Tox. 3, H301 Acute Tox. 3, H331 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=10)	-
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M)IT/MIT (3:1))	CAS: 55965-84-9 Index: 613-167-00-5	≤0.0014	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) EUH071 See Section 16 for the full text of the H statements declared above.	-

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Notes, if applicable, refer to Notes given in Annex VI of 1272/2008/EC.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Show this safety data sheet or label to the doctor if possible.
- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with plenty of lukewarm water, keeping eyelids open. Continue to rinse for at least 15 minutes.
- Inhalation** : Remove to fresh air.
- Skin contact** : Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious). If significant amounts have been swallowed or if symptoms persist, seek medical attention.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Contains:

1,2-benzisothiazol-3(2H)-one (BIT)

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M)IT/MIT (3:1))

2-Octyl-2H-isothiazol-3-one (OIT)

May produce an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire. Recommended: Alcohol resistant foam, CO₂, powders or water spray/mist.
- Unsuitable extinguishing media** : Do not use a direct water jet that could spread the fire.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : This product is not classified as flammable. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
- Hazardous combustion products** : When exposed to high temperatures, hazardous decomposition products may be produced, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Use water spray to keep fire-exposed containers cool. This material is hazardous to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Special protective equipment for fire-fighters** : Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures** : Refer to protective measures listed in sections 7 and 8.
- 6.2 Environmental precautions** : Hazardous to aquatic environment. Do not allow to enter drains, water courses or soil.
- 6.3 Methods and material for containment and cleaning up** : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Preferably clean with water or detergent. Avoid using solvents.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling** : Skin contact with the product and exposure to spray mist and vapor should be avoided. Avoid contact with skin and eyes. Avoid inhalation of dust from sanding. See Section 8 for information on appropriate personal protective equipment. Eating, drinking and smoking should be prohibited in areas where this material is handled and stored. Wash hands before breaks and immediately after handling the product. Avoid release to the environment.
- 7.2 Conditions for safe storage, including any incompatibilities** : Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Recommended storage temperature is +5°C ...+25°C. Do not allow to freeze. Store in accordance with local regulations.
- 7.3 Specific end use(s)** : None.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
2-(2-butoxyethoxy)ethanol	EH40/2005 WELs (United Kingdom (UK), 8/2018). TWA: 10 ppm 8 hours. TWA: 67.5 mg/m ³ 8 hours. STEL: 15 ppm 15 minutes. STEL: 101.2 mg/m ³ 15 minutes.
propylene glycol	EH40/2005 WELs (United Kingdom (UK), 8/2018). TWA: 10 mg/m ³ 8 hours. Form: Particulate TWA: 474 mg/m ³ 8 hours. Form: Sum of vapour and particulates TWA: 150 ppm 8 hours. Form: Sum of vapour and particulates

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

DNELs/DMELs

No DNELs/DMELs available.

PNECs

No PNECs available

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Comply with the health and safety at work laws.

Individual protection measures

- Eye/face protection** : Safety eyewear should be used when there is a likelihood of exposure. Use safety eyewear (EN166), especially during spray-application.
- Hand protection** : Wear protective gloves. Gloves should be replaced regularly and if there is any sign of damage to the glove material. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.
Recommended glove material (EN374):
> 8 hours (breakthrough time): nitrile rubber
Not recommended: PVA gloves
- Skin protection** : Wear appropriate personal protective clothing to prevent skin contact.
- Respiratory protection** : If ventilation during spray-application is inadequate, use respirators with combination filter AP, gas/dust filter (EN405:2001). Wear a respirator with type P2 filter during sanding (EN149:2001). Be sure to use an approved/certified respirator or equivalent. Check that mask fits tightly and change filter regularly.
- Environmental exposure controls** : For information regarding environmental protection measures, please refer to section 13 for waste handling, section 7 for handling and storage and section 1.2 for relevant identified uses of the substance or mixture and uses advised against.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Colour** : Various
- Odour** : Mild.
- Odour threshold** : Not relevant for the hazard assessment of the product.
- pH** : Not relevant for the hazard assessment of the product.
- Melting point/freezing point** : 0°C (water)
- Initial boiling point and boiling range** : 100°C (water)
- Flash point** : > 100 °C
- Evaporation rate** : Not relevant due to the nature of the product.
- Flammability (solid, gas)** : Not applicable. Product is a liquid.
- Upper/lower flammability or explosive limits** : No flammable ingredients present.
- Vapour pressure** : 3.2 kPa [room temperature] (water)
- Vapour density** : Not relevant for the hazard assessment of the product.
- Density** : 1 to 1.3 g/cm³
- Solubility(ies)** : Miscible in water.
- Partition coefficient: n-octanol/ water** : Not available.
- Auto-ignition temperature** : Not relevant due to the nature of the product.
- Decomposition temperature** : Not relevant for the hazard assessment of the product.
- Viscosity** : Not relevant for the hazard assessment of the product.
- Explosive properties** : No explosive ingredients present.
- Oxidising properties** : No oxidising ingredients present.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

- 10.1 Reactivity** : See Section 10.5.
- 10.2 Chemical stability** : Stable under recommended storage and handling conditions (see Section 7).
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : Avoid extreme heat and freezing.
- 10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions:
oxidising agents
strong acids
strong alkalis
- 10.6 Hazardous decomposition products** : When exposed to high temperatures, hazardous decomposition products may be produced, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

There is no testdata available on the product itself.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Long term exposure to spray mist may produce respiratory tract irritation. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
1,2-benzisothiazol-3(2H)-one (BIT)	LD50 Oral	Rat	1020 mg/kg	-
2-Octyl-2H-isothiazol-3-one (OIT)	LD50 Dermal	Rabbit	690 mg/kg	-
zinc pyrithione	LD50 Oral	Rat	550 mg/kg	-
	LD50 Oral	Rat	269 mg/kg	-
	LD50 Oral	Rat	53 mg/kg	-
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M)IT/MIT (3:1))	LD50 Oral	Rat	53 mg/kg	-

Not classified.

Irritation/Corrosion

Not classified.

Sensitisation

The product is not classified as sensitizing by skin contact, but it contains following preservatives or other biocides which may produce an allergic reaction:

1,2-benzisothiazol-3(2H)-one (BIT)

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M)IT/MIT (3:1))

2-Octyl-2H-isothiazol-3-one (OIT)

terbutryn

Mutagenicity

Not classified.

Carcinogenicity

Not classified.

Reproductive toxicity

Not classified.

Teratogenicity

Not classified.

Specific target organ toxicity (single exposure)

Not classified.

Specific target organ toxicity (repeated exposure)

Not classified.

Aspiration hazard

Not classified.

SECTION 12: Ecological information

Ecological testing has not been conducted on this product.
Do not allow to enter drains, water courses or soil.

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.
Harmful to aquatic life with long lasting effects.

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
ammonia	LC50 0.53 mg/l	Fish	96 hours
1,2-benzisothiazol-3(2H)-one (BIT)	Acute EC50 0.36 mg/l	Algae - Skeletonema costatum	72 hours
	Acute LC50 0.74 mg/l	Fish	96 hours
terbutryn	Acute EC50 2 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
2-Octyl-2H-isothiazol-3-one (OIT)	EC50 0.32 mg/l	Daphnia - Daphnia magna	48 hours
	LC50 0.047 mg/l	Fish - Oncorhynchus mykiss	96 hours
zinc pyrithione	EC50 0.0082 mg/l	Daphnia	48 hours
	LC50 0.0026 mg/l	Fish - Pimephales promelas	96 hours

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
2-(2-butoxyethoxy)ethanol	-	92 % - 28 days	-	-
Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability	
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M) IT/MIT (3:1))	-	-	Readily	
2-(2-butoxyethoxy)ethanol	-	-	Readily	

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	Bioconcentration factor [BCF]	Potential
zinc pyrithione	0.9	11	low
2-Octyl-2H-isothiazol-3-one (OIT)	2.45	-	low
terbutryn	3.74	-	low
2-(2-butoxyethoxy)ethanol	1	<3	low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : Not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : Remove as much product as possible from the tools before cleaning. Liquid residue and cleaning liquids are hazardous waste and must not be emptied into drains or sewage system, but handled in accordance with national regulations. Product residues should be left at special companies which have permission for gathering this kind of wastes.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

Packaging

Methods of disposal : Empty packaging should be recycled or disposed of in accordance with national regulations.

Special precautions : No additional information.

SECTION 14: Transport information

This product is not regulated for carriage according to ADR/RID, IMDG, IATA.

	ADR/RID	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-

14.5 Environmental hazards	No.	No.	No.
-----------------------------------	-----	-----	-----

Additional information

IATA : The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Other EU regulations

Europe inventory : Not determined.

National regulations

15.2 Chemical safety assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 DMEL = Derived Minimal Effect Level
 DNEL = Derived No Effect Level
 EUH statement = CLP-specific Hazard statement
 PBT = Persistent, Bioaccumulative and Toxic
 PNEC = Predicted No Effect Concentration
 RRN = REACH Registration Number
 vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

	Classification	Justification
	Aquatic Chronic 3, H412	Calculation method
Full text of abbreviated H statements	: H301 H302 H310 H311 H330 H331 H314 H318 H319 H315 H317 H335 H400 H410 H411 H412 EUH071	Toxic if swallowed. Harmful if swallowed. Fatal in contact with skin. Toxic in contact with skin. Fatal if inhaled. Toxic if inhaled. Causes severe skin burns and eye damage. Causes serious eye damage. Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects. Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]	:	Acute Tox. 2	ACUTE TOXICITY - Category 2
		Acute Tox. 3	ACUTE TOXICITY - Category 3
		Acute Tox. 4	ACUTE TOXICITY - Category 4
		Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
		Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
		Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
		Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
		Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
		Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
		Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
		Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
		Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
		Skin Sens. 1	SKIN SENSITISATION - Category 1
		Skin Sens. 1A	SKIN SENSITISATION - Category 1A
		STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Date of issue/ Date of revision : 10/2/2020

Date of previous issue : No previous validation

Version : 1

Notice to reader

This Safety Data Sheet is prepared in accordance with Annex II (EU) No 830/2015 to Regulation (EC) No 1907/2006 (REACH). The information contained in this Safety Data Sheet is based on the present state of knowledge and current EU and national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.