

Presto Window Putty

Presto Window Putty

DESCRIPTION Waterborne, recoatable quick-drying special glazing putty for interior and exterior windows and doors.

PRODUCT FEATURES Window glazing and filling of small cracks and crevices on wooden substrates. Also suitable for glass, paint, PVC and zinc-coated steel surfaces.



Also suitable for sealing joints in interior walls and ceilings and filling of small cracks. Can be recoated with Tikkurila interior wall and ceiling paints.

RECOMMENDED USES Interior and exterior window frames. Recoatable with e.g. Unica Akva, Teho Window Paint, Helmi Furniture Paint or Maalarin Valkolakka.

TECHNICAL DATA



Colour Range	Off-white
Coverage	100 g/m
Can sizes	300 ml tube
Thinner	Water
Application method	Application with sealing gun
Drying time at 23°C and 50% relative air humidity	The putty is surface dry after 1-2 hours. Recoatable at the earliest after 8 hours from application. The final curing takes 2-10 days depending on conditions and film thickness.
Density	1.6 kg/l, ISO 2811
Storage	Protect from frost
Product code	001 6569

Presto Window Putty

APPLICATION DETAILS

Application conditions	The surface to be treated must be dry, the temperature at least +5 C, and the relative humidity of the air below 80 %.
Preparation	Remove loose and flaking putty and paint with a scraper from the groove and wood surface. Sand and wire brush the surface clean.
Application	Prime exterior bare wood surfaces of grooves with Valtti Base or Valtti Akvabase. Apply a priming coat of Unica Akva or Teho Window Paint on exterior surfaces and Unica Akva, Helmi Primer, Jehu or Otex on interior surfaces. Cut the tube tip diagonally with a knife big enough to make sure that the putty fills the whole groove with one application. Place the tube in the sealing gun and apply directly from the tube to the groove. Apply a finishing coat of Unica Akva or Teho Window Paint on exterior surfaces and Unica Akva, Helmi Furniture Paint or Maalarin Valkolakka 2 times on interior surfaces at the earliest 8 hours from the application of putty. The paint must overlap 1-2 mm onto the window glass.
Cleaning of tools	Clean the tools with water and soap

HEALTH AND SAFETY LABELLING according to Regulation (EC) No. 1272/2008

Contains: 2-(2-Heptadec-8-enyl-2-imidazolin-1-yl)ethanol Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Keep out of the reach of children. Do not empty into drains. A Safety Data Sheet is available on request.

 [Safety Data Sheet - PRESTO Window Putty Ikkunakitti](#)

ENVIRONMENTAL and WASTE DISPOSAL

Empty cans should be recycled or disposed of in accordance with local regulations. Liquid waste should be destroyed according to the local regulations.

TRANSPORT

VAK/ADR -

[Back](#)