

Valtti Pohjuste

DESCRIPTION Priming oil for use on exterior wood.

PRODUCT FEATURES

For protection and priming of timber and wooden structures before surface treatment. Suitable for sawn and planed timber, woodwork, logs, thermally treated and impregnated wood in exterior use.



Finishing coats are recommended to be applied as soon as possible, because colourless priming oil does not protect the wood surface from the adverse effects of sunlight.

RECOMMENDED USES All wooden structures to be treated with wood stains or paints (except surfaces to be treated with wood oils and barn-red paints).

TECHNICAL DATA



Colour Range Colourless

Coverage 4-5 m²/litre on sawn wood surface. 8-10 m²/l on planed wood surface.

Can sizes 0.9 L, 2.7 L and 9 L

Application method Brush, dipping or spray.

Drying time at 23°C and 50% relative air humidity Normally touch-dry in ½ hour and recoatable after 24 hours.

Solids volume 15 %

Density approx. 0.8 kg/l, ISO 2811.

Storage Unaffected by cold storage. Poorly closed or short canisters do not endure long storing.

Product code 005 0500

Valtti Pohjuste

APPLICATION DETAILS

Application conditions	The surface must be dry, the temperature of the air at least +5 oC during treatment and drying, and the relative humidity of the air below 80 %.
Preparation	Remove dirt, mould and any loose material. If needed, use Mould Removal (Homeenpoisto) or Tehopesu (Power Clean) solution according to directions of use. Protect other surfaces and plants from splashes of Valtti Pohjuste.
Diluting	Use unthinned.
Priming	Treat wood surfaces with Valtti Pohjuste in as early construction phase as possible. Apply by brush, dipping or spray. Treat end-grain carefully.
	Apply the finishing coat as soon as possible. If the surface treatment is anyhow delayed, prime the surfaces again before finishing.
	In spray application protect other surfaces and plants from splashes.
Cleaning of tools	Clean immediately after use with White Spirit 1050 or with Tikkurila Tool Cleaner (Tikkurila Pensselipesu).

HEALTH AND SAFETY LABELLING according to Regulation (EC) No. 1272/2008

Harmful x Contains: Naphtha, hydrotreated heavy, and 2-octyl-2H-isothiazol-3-one. FLAMMABLE. HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED. MAY CAUSE SENSITIZATION BY SKIN CONTACT. Do not breathe vapour/spray. Use only in well-ventilated areas. Avoid contact with skin. Wear suitable protective gloves. If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label. Keep out of reach of children. A Material Safety Data Sheet is available on request. [Safety Data Sheet - Valtti Pohjuste](#)



Harmful

ENVIRONMENTAL and WASTE DISPOSAL	Avoid spillage into drains, water systems and soil. Recycle empty, dry cans or dispose of them in accordance with local regulations. Destroy liquid waste according to the local regulations for hazardous waste. Risk of self-ignition! Cleaning cloths, sanding dust or overspray containing the product can create fire by self-ignition. Waste like this should be collected and stored in water before disposal, or dried preferably outdoors or incinerated immediately.
TRANSPORT	ADR: 3 III

sre101110 / akk311210 / lko191106 // 0050500

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

[Back](#)