



PIRTTI interior wood stain

DESCRIPTION Waterbased acrylic latex stain for staining of interior surfaces according to instructions for use.

EXAMPLES OF USE Walls, ceilings, doors, floors and other wooden surfaces.

TECHNICAL DATA

Coverage 10 - 16 m²/l depending on the timber species as well as porosity and roughness of the timber.

Density 1.0 kg/l.

Thinner Water

Application Sponge, brush, or spray.

Drying time at 23 °C, relative humidity of the air 50 % Dust dry in 1-2 hours. The following stain coat or topcoat after 4-6 hours.

Base Paints EP.

Colour Range Tikkurila Interior Wood Stains and Lacquers colour card.

Resistance **Light:** Good.

Storage and transport Protect from frost.

Packaging 0.9 l, 2.7 l, 9 l.

PIRTTI interior wood stain

DIRECTIONS FOR USE

Pretreatment	Sand new wooden surfaces and remove the sanding dust. Sand previously coated surfaces to bare wood.
Staining conditions	The surface to be stained must be dry, the temperature of the air at least +5 °C, and the relative humidity of the air below 80 %.
Staining	<p>Stir Pirtti thoroughly before and occasionally during application to ensure that the colourant/flattening agent is well-mixed in the product. Make a test application on a piece of wood to ensure that the colour of a tinted product is correct. The final colour of the surface depends on timber species, hardness of timber, its original colour, and the number of treatments.</p> <p>Apply one coat with a sponge, brush or spray. Treat the entire surface in one go to avoid overlapping, large panel surfaces a few boards at a time to prevent colour differences. A lighter shade is achieved by thinning the stain with e.g. equal amount of water. If a darker shade is desired, apply another coat when the first one has dried.</p> <p>When the surface is fully dry, apply protective lacquering with Kiva gloss, semi-gloss or matt..</p>
Cleaning of tools	Clean tools with water.
HEALTH AND SAFETY CLASSIFICATION according to EC Directive 88/379/EEC	<p>Not classified as hazardous for health. Handle with care. Avoid prolonged contact with skin and breathing of spray mist.</p> <p>A Material Safety Data Sheet is available at request.</p>
TRANSPORT INFORMATION	ADR/RID -

EKE200893/toI070693/mlr051197/EC100901/890-s

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.