Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU)

2015/830 - Europe

Date of issue/ Date of Date of previous issue 9/28/2020 : 3/6/2018

revision



SAFETY DATA SHEET

Rubber

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name : Rubber

Product description : Water-based roof coating.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Painting work

1.3 Details of the supplier of the safety data sheet

Manufacturer or Distributor

Tikkurila Ovi P.O. Box 53 FI-01301 VANTAA

FINLAND

Telephone +358 20 191 2000

e-mail address of person : Tikkurila Oyj, Product Safety, responsible for this SDS

e-mail: productsafety@tikkurila.com

1.4 Emergency telephone number

Telephone number : 112

(24h)

Supplier or Manufacturer

Telephone number **T**íkkurila Oyj

+358 20 191 2000 (GMT +2) Mon-Fri 8-16

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aguatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

2.2 Label elements

Signal word : No signal word.

Hazard statements : H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

General : Not applicable.

Prevention : P273 - Avoid release to the environment.

: Not applicable. Response **Storage** : Not applicable. **Disposal** : Not applicable.

Supplemental label

: Contains 1,2-benzisothiazol-3(2H)-one (BIT), 2-octyl-2H-isothiazol-3-one (OIT) and elements reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-

3-one (3:1) (C(M)IT/MIT (3:1)). May produce an allergic reaction.

Version 1/10 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Treated articles

This product contains a biocidal product for the preservation of the product during storage. Contains C(M)IT/MIT (3:1). Wear protective gloves.

2.3 Other hazards

Other hazards which do not result in classification

: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

			Classification	
Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Notes
aruminium powder (stabilised)	REACH #: 01-2119529243-45 EC: 231-072-3 CAS: 7429-90-5 Index: 013-002-00-1	≤3	Flam. Sol. 1, H228	Т
2-(2-butoxyethoxy)ethanol	REACH #: 01-2119475104-44 EC: 203-961-6 CAS: 112-34-5 Index: 603-096-00-8	≤3	Eye Irrit. 2, H319	-
1,2-benzisothiazol-3(2H)-one (BIT)	EC: 220-120-9 CAS: 2634-33-5	<0.05	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411	-
terbutryn	EC: 212-950-5 CAS: 886-50-0	<0.025	Acute Tox. 4, H302 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)	-
2-octyl-2H-isothiazol-3-one (OIT)	EC: 247-761-7 CAS: 26530-20-1 Index: 613-112-00-5	<0.01	Acute Tox. 4, H302 Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)	-
zinc pyrithione	REACH #: 01-2119511196-46 EC: 236-671-3 CAS: 13463-41-7	<0.01	Acute Tox. 3, H301 Acute Tox. 3, H331 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=10)	-
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M)IT/MIT (3:1))	CAS: 55965-84-9 Index: 613-167-00-5	<0.001	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) EUH071	-
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the substance and hence require reporting in this section.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Version : 2 2/10

Date of issue/Date of revision 28.09.2020 Date of previous issue 06 03 2018 Rubbei

Notes, if applicable, refer to Notes given in Annex VI of 1272/2008/EC.

SECTION 4: First aid measures

4.1 Description of first aid measures

General : In all cases of doubt, or when symptoms persist, seek medical attention. Show this

safety data sheet or label to the doctor if possible.

Check for and remove any contact lenses. Immediately flush eyes with plenty of Eye contact

lukewarm water, keeping eyelids open. Continue to rinse for at least 15 minutes.

Inhalation

Skin contact : Wash skin thoroughly with soap and water or use recognized skin cleanser. Do

NOT use solvents or thinners.

: If accidentally swallowed rinse the mouth with plenty of water (only if the person is Ingestion

conscious). If significant amounts have been swallowed or if symptoms persist,

seek medical attention.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

contains:

1,2-benzisothiazol-3(2H)-one (BIT)

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M)IT/MIT (3:1))

2-octyl-2H-isothiazol-3-one (OIT) May produce an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire. Recommended: Alcohol resistant foam, CO₂, powders or water spray/mist.

Unsuitable extinguishing media

: Do not use a direct water jet that could spread the fire.

Hazards from the substance or mixture

: This product is not classified as flammable. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Hazardous combustion products

: When exposed to high temperatures, hazardous decomposition products may be produced, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Use water spray to keep fire-exposed containers cool. This material is hazardous to aquatic organisms. Fire water contaminated with this material must be contained

and prevented from being discharged to any waterway, sewer or drain.

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

5.2 Special hazards arising from the substance or mixture

6.1 Personal precautions, protective equipment and emergency procedures

: Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

: Hazardous to aquatic environment. Do not allow to enter drains, water courses or soil.

Version

Date of issue/Date of revision	28.09.2020 Date of previous issue	06.03.2018.	Rubber	

6.3 Methods and materials for containment and cleaning up

: Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Preferably clean with water or detergent. Avoid using solvents.

6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

: Skin contact with the product and exposure to spray mist and vapor should be avoided. Avoid contact with skin and eyes. Avoid inhalation of dust from sanding. See Section 8 for information on appropriate personal protective equipment. Eating, drinking and smoking should be prohibited in areas where this material is handled and stored. Wash hands before breaks and immediately after handling the product. Avoid release to the environment.

7.2 Conditions for safe storage, including any incompatibilities

: Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep container tightly closed. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Recommended storage temperature is +5°C ...+25°C. Do not allow to freeze. Store in accordance with local regulations.

7.3 Specific end use(s) : None.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values	
	EU OEL (Europe, 10/2019). Notes: list of indicative occupational exposure limit values TWA: 67.5 mg/m³ 8 hours. TWA: 10 ppm 8 hours. STEL: 101.2 mg/m³ 15 minutes. STEL: 15 ppm 15 minutes.	

procedures

Recommended monitoring: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

DNELs/DMELs

No DNELs/DMELs available.

PNECs

No PNECs available.

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Comply with the health and safety at work laws.

Individual protection measures

Eye/face protection

: Safety eyewear should be used when there is a likelihood of exposure. Use safety eyewear (EN166), especially during spray-application.

Version : 2

Date of issue/Date of revision 28.09.2020 Date of previous issue

: Wear protective gloves. Gloves should be replaced regularly and if there is any Hand protection sign of damage to the glove material. The instructions and information provided by

the glove manufacturer on use, storage, maintenance and replacement must be

followed.

Recommended glove material (EN374): > 8 hours (breakthrough time): nitrile rubber

Not recommended: PVA gloves

Skin protection : Wear appropriate personal protective clothing to prevent skin contact.

Respiratory protection : If ventilation during spray-application is inadequate, use respirators with

combination filter AP, gas/dust filter (EN405:2001). Wear a respirator with type P2 filter during sanding (EN149:2001). Be sure to use an approved/certified respirator

or equivalent. Check that mask fits tightly and change filter regularly.

Environmental exposure

controls

: For information regarding environmental protection measures, please refer to section 13 for waste handling, section 7 for handling and storage and section 1.2 for relevant identified uses of the substance or mixture and uses advised against.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid. Color : Various Odor : Mild.

Odor threshold : Not relevant for the hazard assessment of the product. pН : Not relevant for the hazard assessment of the product.

Melting point/freezing point Initial boiling point and

boiling range

: 0°C (water) : 100°C (water)

Flash point : >100 °C

: Not relevant due to the nature of the product. **Evaporation rate**

: Not applicable. Product is a liquid. Flammability (solid, gas) Upper/lower flammability or : No flammable ingredients present.

explosive limits

Vapor pressure : 3.2 kPa [room temperature] (water)

Vapor density : Not relevant for the hazard assessment of the product.

Density : 1.2 to 1.3 g/cm³ Solubility(ies) : Miscible in water. Partition coefficient: n-octanol/ : Not available.

water

Auto-ignition temperature : Not relevant due to the nature of the product.

Decomposition temperature : Not relevant for the hazard assessment of the product.

: Not relevant for the hazard assessment of the product. **Viscosity**

Explosive properties : No explosive ingredients present. **Oxidizing properties** : No oxidizing ingredients present.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

: See Section 10.5. 10.1 Reactivity

10.2 Chemical stability : Stable under recommended storage and handling conditions (see Section 7).

10.3 Possibility of hazardous reactions Under normal conditions of storage and use, hazardous reactions will not occur.

Version

Date of issue/Date of revision 28.09.2020 Date of previous issue 06.03.2018. Rubber

10.4 Conditions to avoid : Avoid extreme heat and freezing.

10.5 Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents strong acids strong alkalis

10.6 Hazardous decomposition products

: When exposed to high temperatures, hazardous decomposition products may be produced, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

There is no testdata available on the product itself.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Long term exposure to spray mist may produce respiratory tract irritation. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
7,2-benzisothiazol-3(2H)- one (BIT)	LD50 Oral	Rat	1020 mg/kg	-
2-octyl-2H-isothiazol-3-one (OIT)	LD50 Dermal	Rabbit	690 mg/kg	-
	LD50 Oral	Rat	550 mg/kg	-
zinc pyrithione	LD50 Oral	Rat	269 mg/kg	-
reaction mass of 5-chloro- 2-methyl-2H-isothiazol- 3-one and 2-methyl-2H- isothiazol-3-one (3:1) (C(M) IT/MIT (3:1))	LD50 Oral	Rat	53 mg/kg	-

Not classified.

Irritation/Corrosion

Not classified.

Sensitization

The product is not classified as sensitizing by skin contact, but it contains following preservatives or other biocides which may produce an allergic reaction:

1,2-benzisothiazol-3(2H)-one (BIT)

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M)IT/MIT (3:1)) 2-octyl-2H-isothiazol-3-one (OIT)

terbutryn

Mutagenicity

Not classified.

Carcinogenicity

Not classified.

Reproductive toxicity

Not classified.

Teratogenicity

Not classified.

Specific target organ toxicity (single exposure)

Not classified.

Specific target organ toxicity (repeated exposure)

Not classified.

Aspiration hazard

Version : 2 6/10

Not classified.

SECTION 12: Ecological information

Ecological testing has not been conducted on this product.

Do not allow to enter drains, water courses or soil.

The product is classified as environmetally hazardous according to Regulation (EC) 1272/2008. Harmful to aquatic life with long lasting effects.

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
,2-benzisothiazol-3(2H)- one (BIT)	Acute EC50 0.36 mg/l	Algae - Skeletonema costatum	72 hours
	Acute LC50 0.74 mg/l	Fish	96 hours
terbutryn	Acute EC50 2 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
2-octyl-2H-isothiazol-3-one (OIT)	EC50 0.32 mg/l	Daphnia - Daphnia magna	48 hours
	LC50 0.047 mg/l	Fish - Oncorhynchus mykiss	96 hours
zinc pyrithione	EC50 0.0082 mg/l	Daphnia	48 hours
	LC50 0.0026 mg/l	Fish - Pimephales promelas	96 hours

12.2 Persistence and degradability

Product/ingredient name	Test	Result		Dose		Inoculum
2-(2-butoxyethoxy)ethanol	-	92 % - 28	days	-		-
Product/ingredient name	Aquatic ha	alf-life	Photolysis		Biodeg	radability
reaction mass of 5-chloro- 2-methyl-2H-isothiazol- 3-one and 2-methyl-2H- isothiazol-3-one (3:1) (C(M) IT/MIT (3:1))	-		-		Readily	,
2-(2-butoxyethoxy)ethanol	_		_		Readily	,

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	Bioconcentration factor [BCF]	Potential
zínc pyrithione	0.9	11	low
2-octyl-2H-isothiazol-3-one (OIT)	2.45	-	low
terbutryn	3.74	-	low
2-(2-butoxyethoxy)ethanol	1	<3	low

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

Version : 2 7/10

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : Not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal

: Gather residues into waste containers. Liquid residue and cleaning liquids are hazardous waste and must not be emptied into drains or sewage system, but handled in accordance with national regulations. Product residues should be left at special companies which have permission for gathering this kind of wastes.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

Packaging

Methods of disposal

Empty packaging should be recycled or disposed of in accordance with national

regulations.

Special precautions

: No additional information.

SECTION 14: Transport information

This product is not regulated for carriage according to ADR/RID, IMDG, IATA.

	ADR/RID	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	_	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.

Additional information

IATA

: The environmentally hazardous substance mark may appear if required by other transportation regulations.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

: Not available.

Version

Date of issue/Date of revision 28.09.2020 Date of previous issue 06 03 2018 Rubbei

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Other EU regulations

: At least one component is not listed. **Europe inventory** : Listed

Industrial emissions

(integrated pollution prevention and control) -

Air

VOC Directive : This product is in scope of Directive 2004/42/CE.

15.2 Chemical Safety

Assessment

This product contains substances for which Chemical Safety Assessments are still

required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and

acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation (EC) No.

1272/20081

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification **Justification**

Aquatic Chronic 3, H412 Calculation method

Full text of abbreviated H statements

: H228 Flammable solid. H301 Toxic if swallowed. H302 Harmful if swallowed. H310 Fatal in contact with skin. H311 Toxic in contact with skin.

H330 Fatal if inhaled. H331 Toxic if inhaled.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage. H319 Causes serious eve irritation. H315 Causes skin irritation.

H317

May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

: Acute Tox. 2 ACUTE TOXICITY - Category 2 Acute Tox. 3 ACUTE TOXICITY - Category 3 Acute Tox. 4 ACUTE TOXICITY - Category 4

Aquatic Acute 1 AQUATIC HAZARD (ACUTE) - Category 1 Aquatic Chronic 1 AQUATIC HAZARD (LONG-TERM) - Category 1 Aquatic Chronic 2 AQUATIC HAZARD (LONG-TERM) - Category 2 Aquatic Chronic 3 AQUATIC HAZARD (LONG-TERM) - Category 3

Eye Dam. 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 Eye Irrit. 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2

Flam. Sol. 1 FLAMMABLE SOLIDS - Category 1

Skin Corr. 1B SKIN CORROSION/IRRITATION - Category 1B Skin Corr. 1C SKIN CORROSION/IRRITATION - Category 1C Skin Irrit. 2 SKIN CORROSION/IRRITATION - Category 2

Version 9/10 Date of issue/Date of revision 28.09.2020 Date of previous issue 06.03.2018. Rubber

Skin Sens. 1 SKIN SENSITIZATION - Category 1
Skin Sens. 1A SKIN SENSITIZATION - Category 1A

Date of issue/ Date of

revision

: 9/28/2020

Date of previous issue : 3/6/2018

Version : 2

Notice to reader

This Safety Data Sheet is prepared in accordance with Annex II (EU) No 830/2015 to Regulation (EC) No 1907/2006 (REACH). The information contained in this Safety Data Sheet is based on the present state of knowledge and current EU and national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

Version : 2 10/10