

TIKKURILA

DESCRIPTION	Colour Tester
RECOMMENDED USES	Interior walls and ceilings
PRODUCT FEATURES	Sample of interior wall p

S Sample of interior wall paint in one of the shades out of Tikkurila Symphony tinting system. Sample is presented in full-matt gloss for testing purposes. After you chose the shade at home, remember the code of your colour and check www.tikkurila.com (.fi, .ru) to choose interior paint for walls best suitable for your goals. Find the nearest shop, order and tint the paint into chosen shade. Your wall will be exactly the same shade as this colour sample. Remember that lighting conditions, the smoothness of the paint surface and its gloss can all affect colour perception.



The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.



COLOUR IT

Γ	
TECHNICAL DATA	
Base paints	A BASE, C BASE
Colour Shades	Can be tinted in Tikkurila colors.
Gloss	Full matt.
Coverage	Theoretical coverage 8-12 m²/l. Recommended dry film thickness: 36-46 um. Practical coverage depends on the application method, conditions, shape and roughness of the surface to be treated.
Can sizes	A BASE: 0.18 I C BASE: 0.18 I
Application method	Brush, roller
Drying time	Dust dry after 30 minutes. Recoatable after 1-2 hours.
Density (kg/l)	Approx. 1.3 kg/l depending on shade, ISO 2811.
voc	(cat A/a) 30g/l(2010). Colour It contains less than 2g/l VOC.
Storage	Protect from frost. Badly closed or short cans and/or tinted products do not withstand long storage. Tinted products should be used during the same painting season.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.



COLOUR IT

APPLICATION INSTRUCTIONS

Application conditions

The surface to be painted must be dry, solid and clean. Always use clean roller or brush while painting

Painting

Stir the paint before use

Cleaning of tools

Clean tools with water. Tikkurila Pensselipesu Tool Cleaner is recommended to remove slightly hardened paint.

Environmental protection and waste disposal

Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations.

Health and Safety

The product is not classified as dangerous. Wear protective gloves. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains 1,2-benzisothiazol-3(2H)-one (BIT) and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)). May produce an allergic reaction. This product contains a biocidal product for the preservation of the product during storage. Contains: reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)).

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.