


EC TYPE-EXAMINATION CERTIFICATE

according to Marine Equipment Directive (Module B)



NOTIFIED BODY 0809

This is to certify that Eurofins Expert Services Ltd did undertake the relevant type approval procedures for the type of equipment identified below which was found to be in compliance with the requirements of Marine Equipment Directive (MED) 2014/90/EU and Commission implementing regulation (EU) 2021/1158 subject to any conditions in the schedule attached hereto.

TAIKA Pearl Paint

meet the requirements imposed in IMO 2010 FTP Code, Annex 1 Part 2 and Part 5
(IMO Resolution MSC.307(88) Annex 1 Part 2 and Part 5) on

**materials with low flame-spread characteristics and not
producing excessive quantities of smoke and toxic products
or not giving rise to toxic hazards at elevated temperatures**

and the provisions of Marine Equipment Directive 2014/90/EU, that apply to

surface materials with low flame-spread characteristics.

These products have been assigned a U.S. Coast Guard Module B number (**164.112 / EC0809**) to note type approval to Module B only as it pertains to obtaining U.S. Coast Guard approval as allowed by the "Agreement between the European Community and the United States of America on Mutual Recognition of Certificates of Conformity for Marine Equipment" signed February 27th, 2004 and amended by Decision No.1/2018 signed February 18th 2019.

Manufacturer of the product is

Tikkurila Oyj

The Certificate is valid until September 27, 2026 unless suspended, expired or withdrawn, provided the conditions in this certificate are complied with and the equipment remains satisfactory in service.

Espoo September 27, 2021

This document is electronically approved



Tiina Ala-Outinen
Manager, Building Structures



Heli Välimäki
Senior Expert

EUROFINS EXPERT SERVICES OY

Kivimiehentie 4
FI-02150 ESPOO

Y-tunnus 2297513-2
www.sertifikaattihaku.fi

FINAS
Finnish Accreditation Service
S017 (EN ISO/IEC 17065)

Manufacturer	Tikkurila Oyj Heidehofintie 2 FI-01301 Vantaa Finland.
Regulation Item	MED 1/3.18b surface materials with low flame-spread characteristics, paint systems.
Product description	TAIKA Pearl Paint, Waterborne pearl acrylate paint.
Approved application	On non-combustible non-metal substrates with a density of 665 kg/m ³ or higher and a thickness of 25 mm or greater. On metallic substrates with the thickness of 0,525 mm or greater. The dry film thickness max. 63 µm. On bulkhead, wall and ceiling linings.
Technical document	Taika helmiäismaali, Tuoteseloste 13.7.2021.
Test reports	EUFI29-21003499-T6, (September 14, 2021), Eurofins Expert Services Oy, (on metallic substrates). VTT-S-03609-16, (September 12, 2016), VTT Expert Services Oy, (on non-combustible non-metallic substrates).
Test methods	IMO 2010 FTP Code Annex 1 Part 2 and Part 5 (IMO Resolution MSC.307(88) Annex 1 Part 2 and Part 5).
Notes	This certificate replaces the previous EC Type-Examination Certificates (B-module) VTT-C-11737-15-16. This certificate will not be valid if the manufacturer makes any changes or modifications to the approved equipment, which have not been notified to, and agreed with the notified body named on this certificate. Should the specified regulations or standards be amended during the validity of this certificate, the product is to be reapproved prior to it being placed on board vessels to which the amended regulations or standards apply. The Mark of Conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-control phase module (D, E or F) of Annex B of the Directive is fully complied with and controlled by a written inspection agreement with a notified body.

END OF CERTIFICATE