

## Technical data

**Description:** waterborne paving stain

**Examples of use:** Industrially dyed and uncolored concrete garden stones and slabs. Not recommend for new garden stones or non-absorbing substrates like wash concrete or natural stone.



**Coverage:** 4-8 m<sup>2</sup>/l applied once on concrete stone or slab (depending on the absorbency of the substrate)

**Pack sizes:** 0.9 l, 2.7 l and 9 l

**Gloss Grade:** Undefined

**Application:** Brush, roller or spray. Knapsack spray or similar is recommended for spray application.

**Drying time:** Surface is dry (walkable) after a few hours. Drying is affected by the amount of stain used and the porosity of the surface. If needed, a second coat can be applied when the surface is dry, after a few hours, depending on condition.

## Colors



EK01 Light Grey



EK02 Grey



EK03 Dark Grey



EK04 Black



EK05 Dark Brown



EK06 Purple



EK07 Reddish Brown



EK08 Red



EK09 Light Brown



EK10 Yellow

Above color samples are made on concrete grey garden stones. The colors are as close to reality as printing technology allows.



# PATIO PAVING STAIN

Keeps paving stones in prime condition!

With Tikkurila's waterborne Patio Paving Stain you can easily and quickly renew the look of old paving stones and slabs. Patio Paving Stain helps to align and deepen the color of paving stones.



TIKKURILA OYJ

PL/PO Box 53, FI-01301 Vantaa, Puh./Tel. +358 20 191 2000  
www.tikkurila.com



*Red paving stones before and after, color EK08 Red.*

## PATIO PAVING STAIN

WATERBORNE STAIN FOR CONCRETE GARDEN STONES AND SLABS

Paved areas and paths belong to many outdoor living spaces. Paving is long-lasting and easy to maintain, but it is also exposed to weathering and wear over time. Now industrially colored paving stones are possible to be renovated to give them even and strong color. Alternatively, unstained concrete grey garden stones can be treated with a completely new color.

It is easy and quick to apply Patio Paving Stain. The product does not form any film on the stones, but it is absorbed by its pores. The stones do not become slippery and their characteristic appearance is enhanced.

## Instructions for use

### Pretreatment

Clean surfaces from dirt, dust, moss and lichen. Wash with pressure washer and use Tikkurila Tehopesu Super Clean according to instructions. If the garden stones or slabs are relatively new, use turbo nozzle or at least sufficient pressure to ensure the absorbency of the surface.

### Application

Stir the stain well before and during use. Treat the surfaces evenly and without interruption to avoid overlapping. Make sure that the product is absorbed evenly and thoroughly into the substrate. Avoid applying a thick and paint-like coat.

The stain is applied with a brush, roller or knapsack spray. When knapsack spray is used, the treatment is finalized with a roller or brush, if needed, to ensure that the product penetrates into the pores of the substrate.



## Undyed (concrete) garden stones and slabs:

Apply 1-2 coats of the stain depending on the absorbency of the substrate and desired end result. Normally two coats give the best end result. The stain can be thinned with max. 50 % water, if needed.

## Dyed garden stones and slabs:

Choose a shade close to the color of the stones to be treated. Apply 1-2 coats of the stain depending on the absorbency of the substrate and desired end result. Normally one coat is enough. The stain can be thinned with max. 50 % water, if needed.

See the product data sheet for detailed instructions and technical data.



### Note!

*Paving stones and slabs are exposed to continuous weathering and they may be subject to severe mechanical stress. Therefore they might also need maintenance treatment almost every year.*

*Always do a trial application to find out the most suitable color, application method, amount of thinner and number of coats for the paving stones to be treated.*