



TIKKURILA

PONTTI FLOOR PAINT 60

SEMI-GLOSS TINTABLE WATER-BORNE PAINT FOR WOODEN FLOORS.

DESCRIPTION

Semi-gloss water-borne tintable polyurethane acrylic paint.

RECOMMENDED USES

Wooden floors and stairs in residential, commercial and storage premises. Suitable for floors subjected to slight mechanical and chemical stress for residential buildings.

PRODUCT FEATURES

For interior painting of wooden floors. Also suitable for the maintenance painting of floors previously painted with an alkyd or epoxy paint or lacquer.



The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

PONTTI FLOOR PAINT 60

TECHNICAL DATA	
Base paints	A BASE, C BASE
Colour Shades	Color cards: Symphony Color System, Feel the Color 2020, Deco Grey colour card, Color Now 2023 Can be tinted in Tikkurila colors.
Gloss	Semi-gloss.
Coverage	5–7 m ² /l.
Can sizes	A BASE: 0.9 l, 2.7 l, 9 l C BASE: 0.9 l, 2.7 l, 9 l
Thinner	Water
Application method	Brush or roller.
Drying time	Dust dry in approx. 15 min. Recoatable in approx. 2 h. Ready for light mechanical stress the next day. Full hardness and abrasion properties will be obtained in approx. 2 weeks. Low air temperature and high humidity will increase the opening time of the paint. Avoid laying heavy articles and things which prevent drying – such as carpets – on the floor during the first week.
Density (kg/l)	Approx. 1.1–1.2 kg/l, ISO 2811
Chemical resistance	Well resistant to greases and white spirit, for example. Not resistant to strong solvents such as thinner.
Volume solids (%)	35
VOC	(cat A/i) max. 140 g/l (2010). Pontti Floor Paint 60 contains VOC max. 140 g/l.
Storage	Protect from frost. Protect from frost



PONTTI FLOOR PAINT 60

APPLICATION INSTRUCTIONS

Application conditions

The surface to be painted must be dry, the temperature of the air at least +10°C, and the relative humidity of the air below 80%.

Surface preparation

Bare wooden surfaces:

Remove all dirt, dust, grease and oil.

Previously painted wooden surfaces:

To remove any dirt and possible wax containing washing solution, wash previously painted or lacquered surfaces with Maalipesu cleaning agent diluted with water to a ratio 1:5. Rinse thoroughly with water and allow to dry. Remove old, flaking paint. Sand the surfaces carefully and remove sanding dust.

Painting

Stir the paint well before use.

Bare wooden surfaces:

Apply 1-2 coats of Multistop Isolation Primer on bare wood surfaces. The best insulation result is achieved when the treatment is performed twice. Finish with 1-2 coats of undiluted Pontti Floor Paint 60. Use a synthetic brush.

Previously painted or lacquered surfaces:

Apply Pontti Floor Paint 60 directly on the surface 1-2 times with a synthetic brush.

Note! The paint will dry quickly, so plan your work so as to avoid visible overlapping. Work lengthwise along the boards, treating a few boards at a time. Any patching up should be done when the surface has dried.

Note

ROUGHENING:

To reduce the slipperiness of the painted surface, add one 1/3 l container of Liukueste non-slip powder to 10 liters of unthinned paint. It is sufficient to stir by hand. Use the roughened paint for the last two finishing coats.

The roughened paint can be used for painting the entire floor surface or a part marked off with masking tape. With stairs, for example, you can add an anti-slip strip to the outer edge of each step.

Cleaning of tools

Clean tools with water or Tikkurila Pensselipesu (Tool Cleaner). Tikkurila Pensselipesu Tool Cleaner is recommended to remove slightly hardened paint.

Maintenance instructions

The painted surface will reach its final wear and chemical resistance after approximately 2 weeks from the surface treatment. Avoid cleaning during this period of time. Clean the surface with a brush, a mop or a dust cloth. Dirty surfaces can be cleaned with a cleaning tool and a neutral (pH 6–8) washing solution.

Environmental protection and waste disposal

Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.



PONTTI FLOOR PAINT 60

Health and Safety

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended. Wear protective gloves. Contains 1,2-benzisothiazol-3(2H)-one (BIT). May produce an allergic reaction. This product contains a biocidal product for the preservation of the product during storage. Contains: BIT.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.